

DIMENSION "A": 7" MINIMUM FOR RESIDENTIAL METERS.
9" MINIMUM FOR COMMERCIAL AND APARTMENT METERS.

15" MAXIMUM 15" MAXIMUM

DIMENSION "B": 7" MINIMUM FOR RESIDENTIAL METERS.

9" MINIMUM FOR COMMERCIAL AND APARTMENT METERS.

DIMENSION "C": 2-1/2" MINIMUM FOR RESIDENTIAL METERS.

5" MINIMUM FOR COMMERCIAL AND APARTMENT METERS.

NOTE: DIMENSION "A" APPLIES ONLY TO THAT PORTION OF THE CABINET ENCLOSING DOOR IN FRONT OF THE METER.

NOTE:

- 1. THE CABINET SHOULD BE DESIGNED SO THAT NEITHER THE ROOF NOR THE DOOR SUPPORTS INTERFERE WITH THE INSTALLATION OF THE METER.
- 2. AT LEAST 16" VERTICAL AND HORIZONTAL CLEAR SPACE SHALL BE PROVIDED DIRECTLY IN FRONT OF THE SOCKET (8" ABOVE AND BELOW, AND 8" ON EITHER SIDE OF THE CENTER OF THE METER SOCKET).
- 3. THE CABINET DOORS SHALL HAVE SIDE HINGES, WILL OPEN GREATER THAN 90 DEGREES, AND WILL HAVE A LATCH TO KEEP IT IN THE OPEN POSITION.
- METER CABINET ENCLOSURES INSTALLED IN LOCATIONS SUSCEPTIBLE TO VEHICULAR DAMAGE MUST COMPLY WITH THE REQUIREMENTS OF CPAU STD DWG SR-MT-E-1035.

APPROVED . 199	ENGINEERING STANDARD					
ane 1	CLEARANCE FOR	2	3/16	ADDED NOTE 4		TT
- signeding	METER CABINET ENCLOSURES		11/08	REVISED NOTES AND DIMEN	ISIONS	TT
ENGRAMAGE			DATE	DESCRIPTION		APPR
DRAWN ANDES	CITY OF PALO ALTO	١	NTS	SR-MT-E-1013	1 0	- 1
CHECK PEV	CALIFORNIA	SO	CALE	STANDARD NO.	SHEE	T NO.